



ALPHA-3R – Portable Direct Thermal Receipt Printer

SIMPLIFY YOUR EVERYDAY MOBILE RECEIPT PRINTING NEEDS



KEY FEATURES

- TSC Designed & Manufactured
- IP54-rated environmental case to resist dust and water
- Double-wall plastic design with rubber over-mold construction that withstands 1.5 m (5 ft) drop
- Wired & wireless communication interfaces: USB 2.0, RS-232, Bluetooth, and 802.11 b/g/n
- High capacity 2500 mAh rechargeable Li-ion batteries
- Large paper capacity to reduce the frequency of changing paper roll
- High-speed processor and extensive memory for fast print speeds of up to 100 mm (4") per second
- Lasts more than 12 hours of printing receipts on a single battery charge
- Supports TSPL-EZ (EPL2 and ZPL emulations) plus CPCL emulation
- 2-Year Warranty is longer than other competitor's warranty

APPLICATIONS

- Direct Store Deliveries (DSD)
- Field Repair/Installation
- Mobile Point-of-Sale
- Parking Citations
- Mobile Ticketing
- Onboard Transportation Ticketing
- Utility Billing/Meter Reading

ALPHA-3R – Portable Direct Thermal Receipt Printer

PRINTER MODEL	Alpha-3R
Resolution	8 dots/mm (203 DPI)
Printing method	Direct Thermal
Max. print speed	102 mm (4")/second
Max. print width	72 mm (2.83")
Max. print length	2,286 mm (90")
Enclosure	Double-walled plastic with rubber over molded
Physical dimension	116 mm (W) x 148 mm (H) x 70 mm (D) 4.57" (W) x 5.83" (H) x 2.75" (D)
Weight (including battery)	0.55 kg (1.212 lbs)
Drop specification	1.5 m (5 ft)
IP rating	IP54 (w/case)
Max. roll capacity	57 mm (2.25") OD
Processor	32-bit RISC CPU
Memory	<ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM
Interface	<ul style="list-style-type: none"> • USB 2.0 • 802.11 b/g/n Wireless (factory option) • Bluetooth (factory option) • RS-232 (user option)
Power	Two-cell, 7.4V DC, 2500 mAh Li-ion rechargeable battery
Operation switch, button	<ul style="list-style-type: none"> • 3 buttons (On/off, feed, and cover-open) • 2 color LED for printer status, 3 LEDs for battery status
Sensors	<ul style="list-style-type: none"> • Reflective sensor • Head open sensor
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • One Monotype Imaging® CG Triumvirate Bold Condensed scalable font
Bar code	<ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar • 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec
Printer language	TSPL-EZ (EPL2, ZPL2) & CPCL emulation
Media type	Receipt paper & Bline receipt paper (Black mark in printing side)
Max. media width	80 mm (3.15")
Media thickness	0.0508 ~ 0.1016 mm (2 ~ 4 mil)
Media core diameter	10.2 ~ 19 mm (0.4" ~ 0.75")
Environment condition	Operation: -10 ~ 50 °C (32 ~ 104 °F), 10 ~ 90% non-condensing Storage: -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 93% non-condensing
Safety regulation	FCC, CE, CB, CCC
Environmental concern	Comply with RoHS, WEEE
Accessories	<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • Belt Clip • Li-ion battery • Power adapter
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 25 km (1 million inches)
Factory options	<ul style="list-style-type: none"> • 802.11 b/g/n Wireless network • Bluetooth module
User options	<ul style="list-style-type: none"> • RS-232 cable • USB cable • Li-ion battery • Charge station 1 cell (with changeable power connector) • Vehicle power adapter • IP54-rated environmental case with shoulder strap



de Boelakkers 27A
5591 RA Heeze
T: +31(0)40 - 226 43 91
F: +31(0)40 - 226 44 24
www.parlando.nl