



MOBILE DATA COLLECTION

M₂₆₆

Mobile terminal

Specially developed for the high hygiene regulations within the food industry, the M266 offers a robust and intelligent solution for mobile use. Even in tough IP65 industrial environments, a blue, stable ABS housing is characterised by sufficient protection against dust and jet water as well as increased durability. Thanks to the blue colour, the device can be easily detected when performing checks on food. The M266 is designed without any large dirt-collecting edges and is easy to clean. A brief ambient temperature as low as -18 °C and tested compatibility with different cleaning agents ensure trouble-free work in the field of food production.

Thanks to the simple structure, the M266 is designed in a very clear manner and leads to the utmost acceptance amongst employees. The Windows Embedded CE 6.0* operating system, the powerful processor and a long battery life ensure that work can be carried out flawlessly and economically.

The washable membrane keyboard, six freely-configurable function keys as well as the large, resistive touch screen complete with LED backlight provide you with plenty of options to create your individual solution.

Stock and route optimisation as well as flexibility in terms of service and constant controlling ensure an effective working process and high quality during order processing.



M266

- Robust housing with integrated rubber protection
- 6 freely configurable function keys
- Washable membrane keyboard
- Premium TFT display with LED backlight and resistive touch screen
- Windows Embedded CE 6.0*
- Marvell XScale** processor PXA166; 800 MHz
- WLAN
- BT-compatible close-range network (on request)



MOBILE DATA COLLECTION

M₂₆₆ Mobile terminal

Housing: **ABS** Protection class: **IP65**

Operating temperature: 0 °C to 45 °C (short-time -18 °C)

Storage temperature: -20 °C to 70 °C

Device dimensions: 224 x 92 x 36/157 mm (L x W x H)

Weight: Ca. 590 g

7.2 V/Li-lon change battery, Power supply:

Docking station

3.5" color TFT display with LED backlight, 240 x 320 pixels, 640 cd/m^2 , Display:

Status LED

Touch screen: Resistive, minimum surface hardness of 3H

Washable membrane keyboard, Keyboard:

21 keys incl. 6 function keys

Barcode scanner: 1D scanner integrated in housing (scanner key inside grip)

Marvell XScale** Prozessor PXA 166; 800 MHz Processor:

Memory: 512 MB flash, 256 MB RAM,1 GB microSD flash card,

larger memory optionally available

Operating system: Windows Embedded CE 6.0*

Interfaces: WLAN according to IEEE 802.11a/b/g,

WLAN according to feee 802.11a/b/g,
WLAN Security':
WEP, WPA, IEEE802.11i (Personal and Enterprise), WPA2, WPA2-PSK,
802.1x: PEAP-MSCHAPv2, PEAP-GTC, PEAP-TLS, EAP-TLS, EAP-TLS, EAP-FAST, LEAP,
microSD card (intern, 1 GB plugged),
microUSB (intern)

Optional: 2D-Scanner

BT-compatible close-range network, UMTS, GPS On request:

Zubehör: DS266 docking station



^{*} Registered trademark -Microsoft
** Registered trademark -MARVELL INTERNATIONAL LTD.
'Standard codification validated by ACD
Subject to technical modifications